

LINCAT SILVERLINK PROPANE GAS COUNTER-TOP CHARGRILL - W 600 MM - 17.6 KW

MODEL: CG6/P



Create that distinctive chargrilled flavour and branded appearance without the need for messy lava rocks with the Silverlink 600 Gas Chargrill. Utilising innovative radiants instead, the chargrill experience is much cleaner, while the twin zones make for maximum flexibility. The variable heat control and heat retaining cooking grids produce the clean, sharp chargrilled marks that will make your dishes even more appetizing. It's perfect for cafes, bars and restaurants.

SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CN6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm
- SLS6 Lincat Silverlink 600 Free-standing Floor Stand for units W 600 mm

PRODUCT FEATURES

- Uses radiants which replaces the need for using messy lava rocks
- Twin zones for maximum flexibility
- The variable heat control and heat retaining cooking grids produce the clean, sharp chargrilled marks
- Splashguard to project surrounding surfaces from splashes
- Removable branding bars to allow for easy cleaning and access
- Drip drawer to collect all the cooking liquids to reduce cleaning times







LINCAT SILVERLINK PROPANE GAS COUNTER-TOP CHARGRILL - W 600 MM - 17.6 KW

MODEL: CG6/P

WEIGHTS & DIMENSIONS	
Width	600 mil
Depth	652 mil
Height	414 mil
Weight	35.3 kg

SHIPPING DETAILS	
Ship Width	70 cm
Ship Depth	70 cm
Ship Height	63.5 cm
Ship Weight	38.83 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS			
Primary Energy Source Type	Gas	Gas Inlet Size	0.5 in
Kilowatts	17.6 kW	Gas Inlet Pressure Required	20 mBar
Number of Electrical Conductor Wires	1_	Gas Total BTUs	60051 BTU
Electrical Connection Type	Not Applicable	Gas Consumption at Max Use Per Hour	1.26 m ³
Electrical Plug Type	Not Applicable	1 Gas Total BTUs 6005 able Gas Consumption at Max Use Per Hour 1. able able Total Heat Input at Max Use 14.5 kW, 49500 BT	14.5 kW, 49500 BTU per
Number of Electrical Plugs	Not Applicable		hour
Gas Type	Propane	Energy Saving	No

ADDITIONAL SPECIFICATIONS			
Base Type	Not Applicable	Grate Type	Cast Iron
Burner Material	Stainless Steel	Ignition Type	Pilot Light
Charbroiler Type	Countertop	Legs or Casters	Not Applicable
Control Type	Mechanical, Rotary Control Knob	Number of Burners	2
		Number Of Controls	2
Cooking Area Plate Depth	440 mm	Number of Heating Zones	2
Cooking Area Plate Width	477 mm	Radiant Material	Stainless Steel
Food Production Rate	91 x 115g [4oz] burgers [frozen] per hour	Slide Out Warming Rack	No
		Towel Bar	No

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024







MODEL: CG6/P


BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024

