



SILVERLINK 600

#### PRODUCT OPTIONS AND ACCESSORIES

- SB7 750 GRIDDLE SPLASHB
- CC7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 750 mm
- CN7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 750 mm
- SLS7 Lincat Silverlink 600 Free-standing Floor Stand - for units W 750 mm
- HC7 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 750 mm - 0.5 kW
- HCL7 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 750 mm - 0.75 kW

#### PRODUCT FEATURES

- Flexibility of a half smooth, half ribbed plate to give attractive branding lines to your food whilst being able to cook eggs on the smooth half of the plate
- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- Hard wearing 12 mm thick machined steel plate providing even heat distribution and excellent heat retention
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Removable front drainer drawer which also makes for easy cleaning. Ideal for busy establishments
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up

The Silverlink 600 Electric Griddle is a reliable choice for cooking eggs, bacon, burgers, or vegetables. Featuring a robust 12 mm thick steel plate, it ensures even heat distribution and excellent retention. With two independently controlled heat zones, you can choose to operate one zone during quiet times. The griddle's half smooth, half ribbed plate adds versatility, creating attractive branding lines on food and allowing for egg cooking on the smooth surface. Ideal for cafes, pubs, and restaurants, its thermostatic control ensures accurate temperatures, delivering consistent and delicious results every time.

**WEIGHTS & DIMENSIONS**

Width	750 mil
Depth	620 mil
Height	330 mil
Weight	49.2 kg

**SHIPPING DETAILS**

Ship Width	80 cm
Ship Depth	100 cm
Ship Height	63.5 cm
Ship Weight	60 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

**PRODUCT CERTIFICATIONS**



**ENERGY SPECS**

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	Single Phase 26.1/Three Phase L1=13.0; L2=13.0; L3=N/A	Electrical Connection Type	Direct Hardwired
Electrical Voltage	230 volts/400 volts	Electrical Plug Type	Not Applicable
Electrical Watts	6000	Number of Electrical Plugs	Not Applicable
Electrical Phase	Single, Three	Dedicated Circuit Required	Yes
Kilowatts	6 kW	Energy Saving	No

**ADDITIONAL SPECIFICATIONS**

Control Type	Rotary Control Knob	Number Of Controls	2
Cooking Area Plate Depth	405 mm	Number of Heating Zones	2
Cooking Area Plate Width	712 mm	Plate Shape	Rectangle
Cooking Plate Finish Material Type	Grooved Steel	Plate Thickness	12 mm
Food Production Rate	190 x 115g [4oz] burgers [frozen] per hour	Temperature Maximum	250 °C
Legs or Casters	Not Applicable	Temperature Minimum	50 °C
Lower Platen Surface Type (multi-select)	Smooth and Grooved	Thermostat Element Location	Under Plate Mount

**BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

**TECHNICAL DRAWING**

