



**FREEZY Range**  
**Refrigerator GN 2/1**  
**Lt 1500**

**Range plus:**

- \* Quality performances
- \* Ergonomics and design
- \* Peak reliability and energy saving



Commercial code	FD150
Temperature range	0/+10° C
Technical features	<p>Insulation thickness: 75 mm.CE Mark. Cooling unit at evaporation temperature -10° C and condensation temperature 53,5° C rated at 654W with hermetic compressors. Temperature range inside cell 0° C/+10° C. Maximum room temperature: +43 (Climate Class 5, room +40° C and 40% R.H.). The ventilated refrigeration allows an easy distribution inside the cooling chamber, not directly on the food. The evaporator has been designed to have the maximum surface of heat exchange. Refrigerant fluid: R134a.</p> <p>Copper/aluminium finned evaporator. Completely automatic air defrosting. Easy access to all controls and parts from the control board, that lifts up.</p>
Functional features	<p>One-piece construction entirely in AISI 304 stainless steel.Satin finished door, side panels and control panel. Scotchbrite finishing. Two doors, single refrigerating compartment. One-piece construction with round inner corners, CFC-free expanded polyurethane insulation. Insulation thickness in mm density 40 kg/m<sup>3</sup>, for better thermal properties and impressive energy saving, in mm: 75 side panels; 50 back; 60 door; 75 bottom; 78 ceiling. Doors on stainless steel hinges equipped with a self-closing device for openings inferior to 90°. Key-operated lock. Easily removable magnetic gasket. Ergonomics and design, with the door integrated full-height AISI 304 stainless steel handles. Door integrated full-height AISI 304 stainless steel handle. Depth with door open 1490mm.</p> <p>Easily removable AISI 304 stainless steel 20 positions rack, in 60 mm vertical spacing intervals for guides and/or plastic- coated hooks. Control board, equipped with digital thermometer-thermostat and on/off switch. The board is preset to monitor/memorize the parameters of conservation values. Safety interlock switch on control panel to stop internal fan and switch on compartment light. Compartment light protected and easily accessible. Automatic evaporation of condense drain through heating elements. Standard accessories supplied: 3 plastified shelves GN 2/1 and nr. 12 hooks for shelves. Stainless steel AISI 304 feet, adjustable in height from 115 to 165 mm.</p>
External size	150x83,5x204 cm
Internal size	135x67x144 cm
Electric power	0,52Kw - Allacciamento standard: V - Hz 220V 1N-/60Hz
Gross / Net weight	200 / 180 kg