

700 PLUS 700 litres



Characteristics



A Refrigeration unit

Sparblock plug-in - monobloc ventilated system

B Evaporator

Treated by cataphoresis, 316L stainless steel coil

C Controllore

Capacitive touch screen

D Door

Thickness 60mm, reversible right/left opening, self-closing 110° opening, removable double chamber magnetic gasket

E Insulation thickness

60mm - HFO polyurethane (no CFC, no HCFC)

F Internal finish

AISI 304 stainless steel

G External finish

Protected stainless steel, galvanized back panel and top panel

J Floor support

Stainless steel feet, galvanised external bottom panel

K Rounded corners/removable parts

For easy cleaning




N Lighting

Standard

R Lock

con chiave di serie

Technical drawing and set-up



A Section plane


B Section plane

C Power cable outlet (length 2 m)














WARNING! While installing, have a qualified electrician connect it to an electrical panel.

D Minimum distances

WARNING! The distance from hot appliances (e.g. fryers or ovens) must be at least 50 cm.



Technical specifications

Temperature (°C)	 0/+10	 -2/+10	 -18/-22	 0/+10	 -18/-22
Model	PPCC070TNXX	PPCC070T2XX	PPCC070BTXX	PPCC070TNMRXX	PPCC070BTMRXX
Doors					
Dimensions (mm) L x D x H	720 x 815 x 2080	720 x 815 x 2080	720 x 815 x 2080	720 x 815 x 2080	720 x 815 x 2080
Packaging (mm) L x D x H	750 x 860 x 2240	750 x 860 x 2240	750 x 860 x 2240	750 x 860 x 2240	750 x 860 x 2240
Refrigerant	 R134a	 R134a	 R507 (R404a)	 R134a	 R507 (R404a)
Absorption (W)	410	410	580	30	30
Voltage (V-Hz)	230-1 50/60Hz	230-1 50/60Hz	230-1 50Hz 230-1 60Hz	230-1 50/60Hz	230-1 50/60Hz
Net weight (kg)	111	112	115	98	99
Gross weight (kg)	125	126	129	112	113
Number of trays	3	3	3	3	3

