

600x400 Complementary equipment & Accessories



Prover
Digitally controlled only by *Dynamic ovens*
Capacity: 12 600x400
Pitch: 75 mm
Voltage: 230 V~ 1N - Frequency: 50 / 60 Hz
Electrical power: 2,4 kW
Max. temperature: 50 °C
Dimensions: 862x890x805 WxDxH mm
Weight: 38 Kg

Art.: XL 415



Neutral cabinet
Capacity: 7 600x400
Pitch: 57 mm
Dimensions: 860x772x676 WxDxH mm
Weight: 25 Kg

Art.: XR 258



Prover with manual control
Capacity: 12 600x400
Pitch: 75 mm
Voltage: 230 V~ 1N - Frequency: 50 / 60 Hz
Electrical power: 2,4 kW
Max. temperature: 70 °C
Dimensions: 862x890x805 WxDxH mm
Weight: 38 Kg

Art.: XL 413



Open stand
Dimensions: 842x665x692 WxDxH mm
Weight: 11 Kg

Art.: XR 168



Hood with steam condenser
Digitally controlled only by *Dynamic ovens*
Voltage: 230 V~ 1N
Frequency: 50 / 60 Hz
Electrical power: 200 W
Exhaust chimney diameter: 121 mm
Min. air flow: 550 m³/h; Max. air flow: 750 m³/h
Dimensions: 860x1028x297 WxDxH mm

Art.: XC 418



Lateral support for stand
For model: XR 168
Capacity: 7 600x400
Pitch: 60 mm
Weight: 3 Kg

Art.: XR 727



First installation kit for single oven
The kit contains water drain fittings and U-trap.

Art.: XC 693



Wheels kit with safety chains
For models: XL 415/ XL 413/ XR 258/ XR 168
4 wheels complete Kit:
2 wheels with brake - 2 wheels without brake.

Art.: XR 622



Shower kit

Art.: XC 208



Wheels kit with safety chains
For models: XB 895/ XB 695
4 wheels complete Kit:
2 wheels with brake - 2 wheels without brake.

Art.: XR 624